

Safety Data Sheet for Gritstone Products

Identification of the Substance	§	Medium to fine grained gritstone.
Composition	§	Quartz and Feldspar
Hazards Identification	§	Respirable crystalline silica dust will be released during cutting or surface treatment.
First Aid Measures	§	Inhalation: If irritation occurs, remove the affected person to fresh air and seek medical attention if necessary.
	§	Skin: wash with soap and water.
	§	Eyes: irrigate with copious amounts of water and obtain medical attention if
		irritation persists.
	§	Ingestion: Swallowing small amounts of dust is unlikely to cause significant
		reaction. Do not induce vomiting. Give plenty of water to drink and seek
		medical attention if necessary.
Fire Fighting Measures	§ .	No fire or explosive hazard.
Accidental Release Measures	§	The release of dust into the environment does not constitute a significant environmental hazard, if contained within the site boundary.
Handling and Storage	§	The product should be handled and stored to minimise the creation of airborne dust.
	§	Stacking of pallets and blocks requires care and they must be stable.
	§	Individual blocks may weigh more than 20 Kg and are subject to
Exposure Controls / Personal	c	assessment under the Manual Handling Operations Regulations 1992. Workplace Exposure Limit (WEL) for respirable crystalline silica = 0.1
Protection	§	mg.m ⁻³ (8hr time weighted average)
1 TOLOGUOTI	§	When cutting, wet systems or local exhaust ventilation should be used.
		Respiratory protection equipment may be required in addition to
		engineering controls.
	§	Eye protection should be used to prevent dust entering the eyes.
	§	When manually handling building blocks, the normal protective equipment
		for use on building sites should be used, in particular safety helmets, safety
Physical and Chemical Properties	§	footwear with protective toe caps and abrasive resistant gloves. Solid odourless material. Other chemical properties not applicable under
r nysicai and Chemicai r roperties	3	ambient conditions.
Stability and Reactivity	§	No safety issues relating to stability and reactivity of product under normal conditions.
Toxological Information	§	Prolonged inhalation of dust can lead to the development of respiratory ill
	_	health, in particularly silicosis.
	§	Dust can cause irritation by abrasion to skin and eyes.
Ecological Information	§ §	Dust can cause gastrointestinal irritation if ingested. When used and disposed of as intended, no adverse environmental effects
		are foreseen.
Disposal Considerations	§	Classed as inert for disposal purposes. Disposal of surplus materials must be in accordance with Duty of Care requirements.
Transport Information	§	Classification for conveyance is not required.
Regulatory Information	§	CHIP Regulations 2002: no classification.
-	§	COSHH Regulations 2004. (Occupational exposure limits: HSE Guidance
	_	Note EH40.)
Oth on lafa was attack	§ .	Environmental Protection ACT 1990.
Other Information	§	The information contained within this safety data sheet does not in itself constitute a risk assessment or COSHH assessment.
	§	Employers have a duty to inform employees and others who may be
	3	affected, of the hazards and precautions to be taken regarding the use of
		products covered by this sheet.
	§	Purchasers of these products have a duty to ensure this sheet is passed to
		third parties.
		Attention is drawn to the following:
	§	HSE Construction Information Sheet No 36 Revision 1 - Silica
	§	HSE Construction Sheet No 37 - Handling heavy building blocks
	§	HSE Construction Sheet No 54 - Dust Control on concrete cutting saws
		used in the construction industry
	§	HSE Chemical Hazard Alert Notice 35 – Respirable Crystalline Silica
	§	HSE COSHH Essentials for Stonemasons ST3 – Hand held rotary tools